

32A 4-/5-pole transformer plug
Plug with fuse



Transformer plug



Plug cap

Technical data

Ex-transformer plug acc. to IEC 60309-1/2, up to 415 V

Marking accd. to 94/9/EC	⊕ II 2 G Ex de IIC T5
EC-Type Examination Certificate	PTB 99 ATEX 1041
IECEX Certificate of Conformity	IECEX BKI 04.0006
Marking accd. to IECEx	Ex ed [ia] IIC T6/T5
Permissible ambient temperature	-20 °C to +40 °C
Rated voltage primary	250 V AC
Rated voltage secondary	24 V, 36 V or 42 V/230 V AC
Frequency	50/60 Hz
Power consumption	max. 65 VA
Back up fuse, internal	0.5 A mT, replaceable
Connecting terminals	1 x 1 - 4 mm ²
Protection class	I
Degree of protection accd. to EN 60529	IP54
Enclosure material	glass-fibre reinforced polyester, polyamide

Ordering details

Voltage	h	Type	Weight approx.	Sec voltage	Order No.
32 A transformer plug 4-pole					
200-250 V	 9 h	Transformer plug 65 VA	2.3 kg	42 V	GHG 532 6469 V0000
		Transformer plug 65 VA	2.3 kg	24 V	GHG 532 6469 V5005
32 A transformer plug 5-pole					
380-415 V	 6 h	Transformer plug 65 VA	2.3 kg	42 V	GHG 532 6566 V0000
		Transformer plug 65 VA	2.3 kg	24 V	GHG 532 6566 V5005
		Transformer plug 65 VA	2.3 kg	12 V	GHG 532 6566 V5025
		Transformer plug 65 VA	2.3 kg	230 V	GHG 532 6566 V5023
Plug with fuse					
200-250 V	 6 h	Plug with fuse max. 6.3 A	1.3 kg		GHG 532 7536 V0000
Accessories					
Plug cap 4 pole					GHG 530 1935 R0002
Plug cap 5 pole / plug with fuse					GHG 530 1935 R0005


| 32A 4-/5-pole transformer plug |
| Plug with fuse |



1

Transformer plug

Dimension drawing



Dimensions in mm